



Portable, Upholstered Commode with Wheels and Drop-Arm

Aluminum Shower Chair and Commode with Casters Knocked Down

| Item # | Assembly | Color | UOM |
|-----------|-----------|-------------|------|
| 11120SV-1 | Assembled | Silver Vein | 1/cs |

- Silver-vein-coated steel tubing frame with welded construction
- Easy-to-release arm mechanism allows for safe lateral patient transfers to and from commode
- Swing-away and detachable footrests (sold separately)
- Injection-molded large plastic toilet seat, 7 quart bucket and cover come standard
- Removable, tool-free back
- Rust-resistant, swivel casters (2 with locks)

| specifications | |
|------------------------|--------------------------------------|
| Width | 18.25" between arms 22.25" Outside |
| Seat Dimensions | 17.75" (W) x 17" (D) |
| Height | 19.75" |
| Weight | 22 lbs. |
| Carton Shipping Weight | 25 lbs. |
| Weight Limit | 350 lbs. |
| Warranty | Limited Lifetime |

| accessories | | |
|-------------|--------------------------------------|----------------|
| PSTDSF-TF | Swing-away Tool-free Footrests | 1 pr/cs |
| RTL12085 | Biodegradable Sanitary Commode Liner | 12/bx, 6 bx/cs |

| Item # | UOM |
|-----------|------|
| 11114KD-1 | 1/cs |

- Easy-to-assemble frame
- Padded, open front, vinyl toilet seat (Figure A)
- Aluminum construction is lightweight and durable
- 3" non-skid, rust resistant, swivel casters (2 rear locking) (Figure B)
- Brass push button allows for easy assembly (Figure C)
- Removable, tool-free back
- Plastic arms for added comfort
- Comes with removable 12 qt commode bucket and cover (Figure D)

| specifications | |
|------------------------|----------------------------------|
| Width | 18" between arms 21.5" Outside |
| Seat Dimensions | 16" (W) x 16" (D) |
| Height | 21" |
| Weight | 14 lbs. |
| Carton Shipping Weight | 18 lbs. |
| Weight Limit | 300 lbs. |
| Warranty | Limited Lifetime |

| accessories | | |
|-------------|--------------------------------------|----------------|
| RTL12085 | Biodegradable Sanitary Commode Liner | 12/bx, 6 bx/cs |